

Column Drilling Machines



BS 35

Option 4 5 6 7 8 10 12 13 14 15 16 42

Powerful column drilling machine for universal application. Drilling table with T-slots, adjustable in height via rack and pinion. Table and head-stock swivelling. Motor protection. Cross lever.

Constant capacity	35 mm
Standard capacity	40 mm
Thread capacity	M 30 (Option)
Spindle	MT 4
Spindle travel	150 mm
Spindle to column	280 mm
Spindle to table	85 to 755 mm
Table surface	550 x 400 mm
Column diameter	120 mm
Total height	2020 mm
Weight	350 kg
Pole changing motor	1,3 / 2,3 kW
BS 35	66931
12 Spindle speeds	80 - 1.400 rpm
BS 35	66934
12 Spindle speeds	160 - 2.800 rpm
BS 35 ST	66935
Infinitely variable spindle speed	80 - 1.400 rpm
BS 35 ST	66936
Infinitely variable spindle speed	160 - 2.800 rpm
Column longer by 100 mm	26443
Electric coolant equipment in baseplate with T-slots	26441
Package class	C

BS 35 AV

Option 4 5 6 7 8 10 12 13 14 15 16 42

Strong and precise column drilling machine for production. Electromagnetic clutch for feed. Worktable adjustable via rack and pinion, swivels around column. Base plate with T-slots. Motor protection.

Constant capacity	35 mm
Thread capacity	M 30 (Option)
Spindle	MT 4
Auto-feeds	0,1 - 0,2 - 0,3 mm/rev
Spindle travel	150 mm
Spindle to column	280 mm
Spindle to table	85 to 755 mm
Table surface	550 x 400 mm
Column diameter	120 mm
Total height	2020 mm
Weight	365 kg
Pole changing motor	1,3 / 2,3 kW
BS 35 AV	66938
12 Spindle speeds	80 - 1.400 rpm
BS 35 AV	66939
12 Spindle speeds	160 - 2.800 rpm
BS 35 AVST	66940
Infinitely variable spindle speed	80 - 1.400 rpm
BS 35 AVST	66941
Infinitely variable spindle speed	160 - 2.800 rpm
Column longer by 100 mm	26443
Electric coolant equipment in baseplate with T-slots	26441
Package class	C

42 Roundtable

14178



Ø 475 mm, 360° rotatable for BS 35

NEW:

For **BT 35 ST**, **BT 35 AVST** digital display for rotation speed as standard.